



Slayer Espresso

3-group

The gateway to flavor profiling. With patented flow control, enabled by a precision needle valve, Slayer Espresso gives you the ability to manipulate and transform the flavor of espresso. In the hands of professional baristas, the brew actuator becomes a vital tool for finding the best in any coffee.

Flavor Profiling

Manual operation of 3-position actuator allows total control

Pre-heat Tank

Unlimited steam and ultimate brew temperature stability

Pre-Brew Timers

Automatic pre-brew wetting stage

Shot Mirror

Improves visibility during extraction

Patented Needle Valve

Grind fine with restricted flow rate during pre-brew phase

Custom Options

Personalize with distinct body colors, materials, and wood



Essential Features

- Independent brew tanks
- PID temperature control, adjustable in 0.1° increments
- Electronic V3 grouphead rated to 1 million cycles
- Commercial portafilter with 58-millimeter, 18-gram basket
- Teflon-coated precision shower screens
- Wood handles and actuators
- Hot water tap with mixing valve
- Non-slip feet
- Shot mirror
- External rotary pump

Specifications

- Width: 40.5 inches / 103 centimeters
- Length: 26.5 inches / 67.5 centimeters
- Height: 17 inches / 43.5 centimeters
- Weight: 305 pounds / 139 kilograms (tanks filled)
- Brew tanks: 1.7 liters, 600 watts
- Pre-heat tank: 5.4 liters, 1,000 watts
- Steam tank: 12 liters, 4,500 watts
- Single-phase power: 200-260 volts AC, 50/60 hertz, 35 amps
- Three-phase power (optional): 380-400 volts AC, 50/60 hertz, 22 amps
- Wattage: 7,300 watts



SLAYER®

+1 206 284 7171

SALES@SLAYERESPRESSO.COM

SLAYERESPRESSO.COM